



## Duster 45

### Moisture Free Powerful & Non Abrasive Microscopic Dust Particles Remover

#### Product Description

Duster 45 is a high pressure composition for removing microscopic dust from assemblies. Its high purity formulation and high pressure, moisture free cleaning agent does not scratch plastics, glass, optics, rubber or hardware. It is non-staining, non-conductive, non-corrosive and does not contain any CFCs, chlorinated solvents or ozone depleting chemicals.

#### Applications

Use on all equipment to remove dust in any industrial, marine, aviation electrical/electronic equipment as:

- Photographic equipment
- Watch mechanisms
- Film negatives
- Computers
- Data processing equipment
- Electromechanical instruments
- Printed circuit boards
- Fiber glass connectors
- Communication equipment
- Precision equipment

#### Benefits

- Delivers pure 100% dry, moisture free cleaning agent
- Ideal cleaning agent where solvents cannot be tolerated or are inappropriate cleaning agents
- Non-conductive and safe to use on all metals, plastics, rubbers, optics, glass and delicate components
- Non staining & non-corrosive
- Leaves no residue and blows away microscopic dust, lint, sand, metallic oxides and other soils
- Non abrasive

#### Directions for Use

Do not shake can before or during use and hold can upright while spraying. Clear any liquid residue that may have formed in the dip tube of the valve stem by pressing the actuator. Use short blast spray method. Use extension tube for tight areas. Spray on film negatives only after clearing the valve first. DO NOT SPRAY ON SKIN AS IT MAY CAUSE FROSTBITE.

#### Caution

Extremely flammable contents. Do not spray near naked flame, hot surfaces or energized equipment. Use with adequate ventilation.

## Duster 45

### Technical Properties

|                         |                 |
|-------------------------|-----------------|
| Type                    | Cleaner         |
| Color                   | Clear           |
| Odor                    | Mild ether like |
| Specific Gravity @ 20°C | 0.53-0.55 g/cc  |
| Flash Point             | 0°C             |
| Freezing Point          | -50°C           |
| Solubility              | Nil in water    |
| Vapor Pressure          | 4 bar at 20°C   |
| Percent Volatile        | 100             |
| Evaporation Rate        | Very fast       |

\* of active ingredients

### Available Packaging

- 500 ml aerosol spray

### General

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

### Disposal

All used and unused product should be disposed of in accordance with state regulations.

### Shelf Life

24 months from date of manufacture in sealed condition.

### Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards. Safety data sheet is available from ASV or your local ASV distributor.

### Limited Warranty

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV® product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty.

### ASV MULTICHEMIE PRIVATE LIMITED

Registered Office: W 46, TTC Industrial Area, MIDC Rabale, Navi Mumbai-400 701, INDIA  
Tel: +91 (022) 2764 2514 | E-mail: info@asvmultichemie.com  
MOLYSULF® & ASV® Specialty Lubricants & MRO Technical Chemicals.  
® Registered trademark of ASV Multichemie Private Limited, INDIA.  
THIS PRODUCT IS DEVELOPED AND MANUFACTURED BY US FOR INDUSTRIAL USE ONLY.

Distributed by: