

MATERIAL SAFETY DATA SHEET

SPOTCHECK® DEVELOPER SKD-S2

1. IDENTIFICATION

Company: MAGNAFLUX
Address: 3624 West Lake Avenue, Glenview, Illinois 60026
Telephone No.: 847-657-5300 (Off-Hour Emergency Number - CHEMTREC - 1-800-424-9300).
Product Use: Penetrant inspection developer
Packages: 1 gallon can, 5 gallon pail, 55 gallon drum, aerosol
NFPA Rating: Health 1, Flammability 3, (aerosol 4), Reactivity 0
PIN (Canada): UN 1993
Revision Date: September 5, 2012

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Wt./Wt.%	CAS#	TLV	PEL	LD ₅₀	LC ₅₀
2-propanol	40 – 70	67-63-0	400 ppm	400 ppm	3.6 g/kg(oral/mouse)	Not available
2-propanone	10 – 30	67-64-1	750 ppm	750 ppm	6 g/kg (oral/rat)	Not available
Isobutane (propellant – aerosol only)	30	75-28-5	Not available	1000 ppm	Not available	Not available
Talc	1 - 3	14807-96-6	Not available	2 mg/me	Not available	Not available

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Extremely flammable white liquid and aerosol. Fast evaporating vapors can reach hazardous levels quickly in unventilated spaces.

POTENTIAL HEALTH EFFECTS & SIGNS AND SYMPTOMS OF EXPOSURE:

Skin Contact: Can irritate by removing natural skin oils on long or repeated exposures.
Eyes: Irritating, but does not damage eye tissue.
Inhalation: Causes dizziness and nausea.
Ingestion: Not significant in small (mouthful) amounts.
Medical conditions known to be aggravated by exposure to product: None

4. FIRST AID

Skin Contact: Remove contaminated clothing. Wash exposed areas with soap and water. Use soothing lotion.
Eyes: Rinse carefully under upper and lower eyelids using plenty of water.
Inhalation: Remove to fresh air if dizzy or nauseated.
Ingestion: Do not induce vomiting. Accidental ingestion of a single mouthful is not expected to cause significant harm.
NOTE: In all severe cases, contact physician immediately. Local telephone operators can furnish number of regional poison control center.

5. FIRE HAZARD

Conditions of flammability: Non-aerosol and aerosol: Ignition will occur if used near flames, arcs or other ignition sources.
Flash point: 2°F (-16°C) (Pensky-Martens closed cup).
Flammable limits in air: 2% to 15%.
Extinguishing media: Carbon dioxide, foam, water.
Special fire fighting procedures: Keep containers cool with water spray.
Hazardous combustion products: Soot, oxides of carbon.
Unusual fire hazards: Aerosol cans may burst over 130°F (54°C) and add to existing fire.

6. ACCIDENTAL RELEASE MEASURES

Turn off or remove sources of ignition. Mop up or sweep up with absorbent. (For disposal, see Section 13.)

7. HANDLING AND STORAGE

Avoid breathing vapors. Avoid eye contact. Avoid repeated or prolonged skin contact. Store away from heat source. Do not spray around arcs or flame.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Controls: Use where ventilation will carry vapors away from occupied areas.
Personal protection : Wear safety glasses to protect eyes. Wear nitrile rubber gloves if hand exposure is unavoidable. Respirator with filter if sprayed in enclosed, unventilated space.

MAGNAFLUX

A Division of Illinois Tool Works Inc.
 3624 WEST LAKE AVENUE ■ GLENVIEW, ILLINOIS 60026
 TEL 847.657.5300 ■ FAX 847.657.5388
 www.magnaflex.com

9. **PHYSICAL PROPERTIES**

<i>Initial boiling point (bulk):</i>	132° F (55°C) (ASTM D-86)	<i>Vapor pressure:</i>	Bulk: 150mm @ 100°F (38°C). Aerosol: 65 psi @ 75°F (24°C)
<i>Percent volatile:</i>	90%	<i>Vapor density:</i>	3
<i>Density/sp. gravity:</i>	0.87	<i>Evaporation rate:</i>	0.4 of ether
<i>Water solubility:</i>	90	<i>Appearance:</i>	White liquid
<i>pH:</i>	Neutral	<i>Odor:</i>	Alcohol odor

10. **STABILITY AND REACTIVITY**

<i>Stability:</i>	Stable
<i>Incompatibility:</i>	None
<i>Hazardous decomposition products:</i>	When burning, soot, oxides of carbon
<i>Reactivity:</i>	None

11. **TOXICOLOGICAL INFORMATION**

<i>Carcinogenicity:</i>	Contains no known or suspected carcinogens listed with OSHA, IARC, NTP, or ACGIH.
<i>Threshold limit value (Bulk):</i>	400 ppm
<i>WHMIS information (Canada):</i>	According to available information, the ingredients have not been found to show reproductive toxicity, teratogenicity, mutagenicity, skin sensitization, or synergistic toxic effects with other materials.

12. **ECOLOGICAL INFORMATION**

No data is available on SKD-S2.

13. **DISPOSAL**

Send to a licensed waste facility for proper disposal.	
<i>RCRA:</i>	Hazardous waste.
<i>U.S. EPA Waste Number:</i>	D001

14. **TRANSPORTATION (These are guidelines, in all cases refer to 49 CFR for proper classification)**

U.S. DOT: 49 CFR 172.101 Hazardous Materials Table

	<u>Non-Aerosol</u>	<u>Aerosol</u>
<i>Proper shipping name:</i>	Flammable Liquid, n.o.s. (Isopropanol, acetone)	Consumer commodity
<i>Hazard class or division:</i>	3	ORM-D
<i>Identification No.:</i>	UN1993	None
<i>Packing Group:</i>	II	None

IATA: List of Dangerous Goods

	<u>Non-aerosol</u>	<u>Aerosol</u>
<i>Proper shipping name:</i>	Flammable liquid, n.o.s. (Isopropanol, Acetone)	Aerosols, flammable
<i>Hazard class or division:</i>	3	2.1
<i>Identification No.:</i>	UN1993	UN1950
<i>Packing Group:</i>	II	-

IMDG: General Index

	<u>Non-aerosol</u>	<u>Aerosol</u>
<i>Proper shipping name:</i>	FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL, ACETONE)	AEROSOLS
<i>Hazard class or division:</i>	3.2	2.1
<i>Identification No.:</i>	UN1993	UN1950
<i>Packing Group:</i>	II	-

15. **REGULATORY INFORMATION**

<i>TSCA:</i>	All ingredients are listed in TSCA inventory.
<i>CERCLA:</i>	Reportable quantity (RQ) for Acetone = 5000 lbs.
<i>SARA TITLE III, Section 313:</i>	Acetone.
<i>California Proposition 65:</i>	This product contains trace amount of chemicals known to the State of California to cause cancer and to cause birth defects or other reproductive harm.
<i>WHMIS Class (Canada):</i>	Non-Aerosol: B-2, D-2B - Aerosol: A, B-5, D-2B
Note:	This MSDS has been prepared to meet WHMIS (Canada) requirements with the exception of using 16 headings.

16. **OTHER INFORMATION**

<i>Revision Statement:</i>	Review
<i>Supersedes:</i>	October 26, 2004
<i>Prepared by:</i>	Tamie Simmons, R&D Manager