

No. 1907/2006 (REACH) Printed 17.05.2013

revision 06.05.2013 (GB) Version 8.0

Mould Release Agent, Spray (GB)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Mould Release Agent, Spray (GB)

Code-Nr. 114500

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

Technical Aerosols

1.3. Details of the supplier of the safety data sheet

Manufacturer/distributor WEICON GmbH & Co. KG

Königsberger Straße 255, DE-48157 Münster

Postbox 84 60, DE-48045 Münster

Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244

E-Mail: info@weicon.de Internet: www.weicon.de

Advice Abteilung Angebote, Verkauf, Export

Phone ++49(0)251 / 9322 - 0 E-mail (competent person):

info@weicon.de

1.4. Emergency telephone number

Emergency advice Giftnotruf Bonn: Bei Vergiftungen (in case of poisoning)

Phone ++49(0)228-19 240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to 67/548/EEC or 1999/45/EC

F+; R12 N; R51/53 R66 R67

R-phrases

12 Extremely flammable.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

66 Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

2.2. Label elements

Labelling according to 1999/45/EC

Remarks for labelling

The product is classified and labelled in accordance with EC directives/German regulations on dangerous substances.

F+ Extremely flammable

N Dangerous for the environment

R-phrases

12 Extremely flammable.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.



No. 1907/2006 (REACH) Printed 17.05.2013

revision 06.05.2013 (GB) Version 8.0

Mould Release Agent, Spray (GB)

S-phrases

Do not breathe spray.Do not empty into drains.

51 Use only in well-ventilated areas.

61 Avoid release to the environment. Refer to special instructions/safety data sheets.

Special rules for supplemental label elements for certain mixtures

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Without sufficient ventilation the formation of explosive vapour/air mixtures cannot be excluded. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

2.3. Other hazards

Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

Description

Mixture of active ingredients with propellant

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to 67/548/EEC
106-97-8	203-448-7	butane	10 - 25	F+ R12
109-66-0	203-692-4	pentane	50 - 100	F+ R12; Xn R65; R66; R67; N R51-53
74-98-6	200-827-9	propane	10 - 25	F+ R12
CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
106-97-8	203-448-7	butane	10 - 25	Flam. Gas 1, H220 / Press. Gas
109-66-0	203-692-4	pentane	50 - 100	Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / STOT SE 3, H336 / Aquatic Chronic 2, H411
74-98-6	200-827-9	propane	10 - 25	Flam. Gas 1, H220 / Press. Gas

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

Do not induce vomiting.

Refer to medical treatment.



No. 1907/2006 (REACH) Printed 17.05.2013

revision 06.05.2013 (GB) Version 8.0

Mould Release Agent, Spray (GB)

4.2. Most important symptoms and effects, both acute and delayed

Physician's information / possible symptoms

The following symptoms may occur:

Anaesthetic state

Headache

Confusion

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam

Dry powder

Carbon dioxide

Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Danger of bursting

Fire gas of organic material has to be classed invariably as respiratory poison.

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

Use breathing apparatus with independent air supply (isolated).

Additional information

Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

6.2. Environmental precautions

Do not discharge into the drains or bodies of water..

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

6.4. Reference to other sections

No information available.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink and smoke.



No. 1907/2006 (REACH)
Printed 17.05.2013

revision 06.05.2013 (GB) Version 8.0

Mould Release Agent, Spray (GB)

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Pressurized container.

Do not pierce or burn even after use.

Vapours can form an explosive mixture with air.

Avoid effect of heat.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Further information on storage conditions

Protect from heat and direct solar radiation.

Storage temperature may not exceed 50°C (=122°F).

Store container at cool and aired place.

Keep in a cool place.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
106-97-8	Butane	8 hours	1450	600	EH40/2005
		Short-term	1810	750	
14807-96-6	Talc respirable dust	8 hours	1		EH40/2005

Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
109-66-0	pentane	8 hours	3000	1000	

8.2. Exposure controls

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Breathing apparatus

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves. Glove material specification [make/type, thickness, permeation time/life, wetting resistance]:: Nitrile rubber; 0,4mm;480min; 60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

tightly fitting goggles

Skin protection

protective overalls

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form Colour Odour aerosol yellowish solvent-like



No. 1907/2006 (REACH) Printed 17.05.2013

revision 06.05.2013 (GB) Version 8.0

Mould Release Agent, Spray (GB)

	Value	Temperature	at	Method	Remark
boiling point	-44 °C				
Flash point	-97 °C				
Ignition temperature	285 °C				
Lower explosion limit	1,4 Vol-%				
Upper explosion limit	10,9 Vol-%				
Vapour pressure	8300 hPa				
Relative density	0,61 g/ml	20 °C			
Solubility in water					immiscible
Solvent concentration	94 %				
Solids content	6 %				

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixtures can be generated.

9.2. Other information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Keep away from heat.

Formation of explosive gas/air mixtures.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritability/Sensitization

	Value/Validation	Species	Method	Remark
Irritability skin	non-irritant			



No. 1907/2006 (REACH)
Printed 17.05.2013

revision 06.05.2013 (GB) Version 8.0

Mould Release Agent, Spray (GB)

Value/Validation Species Method Remark

Irritability eye non-irritant

Skin sensitization non-sensitizing

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

Labelling in compliance with the assessment procedure specified in the EC guidelines 1999/45/EC.

SECTION 12: Ecological information

12.1. Toxicity

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6. Other adverse effects

General regulation

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No.

Name of waste

15 01 10*

packaging containing residues of or contaminated by dangerous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 91/689/EEC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

SECTION 14: Transport information

Land and inland navigation transport ADR/RID

UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS, Classification code: 5F

transport in "limited quantities" according to 3.4 ADR is possible

Marine transport IMDG

UN 1950 AEROSOLS (PENTANE), 2.1

MARINE POLLUTANT: Yes

Air transport ICAO/IATA-DGR

UN 1950 Aerosols, flammable, 2.1

ENVIRONMENTALLY HAZARDOUS: Yes

Transport/further information

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank Lutz Harder GmbH)



No. 1907/2006 (REACH)
Printed 17.05.2013

revision 06.05.2013 (GB) Version 8.0

Mould Release Agent, Spray (GB)

Special precautions for user

No information available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

Remark

Daten separat anfragen / Request data separately.

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Sources of key data used

Danish MAL Code 2-1 VOC-CH 94,00%

Wording of the R/H-phrases specified in chapter 3 (not the classification of the mixture!)

R 12 Extremely flammable.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 65 Harmful: may cause lung damage if swallowed.

R 66 Repeated exposure may cause skin dryness or cracking.

R 67 Vapours may cause drowsiness and dizziness.

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.