Product information

PI 7/09/03/2016

Leak Finder Spray

Description
Leak Finder Spray is a leak test fluid for compressed air, oxygen systems and CNG gas vehicles. Once the fluid is sprayed onto the surface, it indicates where the leaks are by forming bubbles over them.

Properties
- biologically degradable
- environmentally friendly
- miscible with water
- high capacity
- outstanding foaming behavior

Technical data

Compatibility with plastics, resistance to stress cracking	Nicht mit jeder Kunststoffsorte verträglich, bei Polyamid ist eine Rißbildungmöglich (Spannungsrisskorrosion) / Not compatible with all plastics. Crack formation possible with polyamide (stress-corrosion cracking)
Compatibility with materials (seals)	verträglich / compatible DIN 30660
Compatibility with materials (lubricants)	verträglich / compatible DIN 3536
Active agent content	>98,5 %
Foam stability	~ 80 %
Compatibility with materials (PE pipes)	verträglich / compatible DIN 30657
Corrosion according to DIN 30660	keine Korrosion an Eisen, Zink, Zinn, Kupfer, Messing, Aluminium / no corrosion on iron, zinc, tin, copper, brass and aluminium
Density at 20 °C	0,99-1,01 g/cm³
Odor	schwach / slightly
Form	aerossol, flüssig / aerosol liquid
Color / appearance	farblos / colourless
pH value	6-7,5

Areas of application
Motor vehicle maintenance
Repair work on compressed-air brake systems on HGVs, buses and commercial vehicles; welding equipment.

Industry
Test and maintenance work on compressed air and all gas lines including oxygen.

Medicine
Testing OP fittings for anaesthetic apparatus and resuscitating equipment.

Household and sport
Domestic and municipal gas lines, diving equipment and camping equipment.

Application
Spray an appropriate amount of Leak Finder Spray onto the components to be tested.

Available pack sizes

400 ml Can aerosol	3350 D-GB-I-E-P
400 ml Can aerosol	1809 D-NL-F-GR-ARAB
400 ml Can aerosol	2836 GB-DK-FIN-N-S

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUIMOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Postfach 2829
89018 Ulm
Germany

Phone: +49 (0)731/1420-13
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Service-hotline: 0800/8323230
Technical hotline: +49 (0)731/1420-871
www.liqui-moly.de