

## White Universal Grease

### Description

White Universal Grease has been developed for use on high-load plain, roller and rocker bearings. The solid lubricants contained in the product guarantee high load-carrying capacity for clean lubrication points and longlife lubrication. Hygienically quite safe according to the § 31, para. 1, the food and utility items law.

### Properties

- has a lasting effect
- outstanding slip properties
- increases the lubricating effect

### Technical data

Color / appearance	weiß / white
Base	Mineralöl mit Kombination weißer Festschmierstoffe / mineral oil with a mixture of white solid lubricants
Thickener	Lithiumhydroxystearat
Viscosity at 40 °C	110 mm <sup>2</sup> /s DIN 51562-1
Density at 20 °C	0,93 g/cm <sup>3</sup> DIN EN ISO 3838
NLGI number	2 DIN 51818
Worked penetration	265-295 DIN ISO 2137
Dropping point for the solids	> 195 °C DIN ISO 2176
Operating temperature range	-30 bis +120 / -30 to +120 °C
Festschmierstoff	Titandioxid
Water resistance at 90 °C	1 - 90 DIN 51807/T1
Emcor corrosion class	0 DIN 51802 1 - 100 (Kupfer) / 1 - 100 (copper) DIN 51811
Four-ball tester material load/weld force	3.600 N DIN 51350-4
Four-ball tester wear/indentation diameter	<1 mm DIN 51350-5
Odor	Mineralöl / mineral oil

### Technical data

Form pastös, flüssig / pastelike, liquid

### Areas of application

Suitable for lubricating high-load plain, roller and rocker bearings, spindles and guides on machines in the food, drinks, paper, textile and clothing industries as well as on domestic appliances.

### Application

As usual for grease. Do not mix with other greases.

### Available pack sizes

400 g Cartridge plastic 8918  
D-NL-F-GR-ARAB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

