

## **RNC 3200 RustoNil**

## rust removing compound for steel

**RNC 3200 RustoNil** is an inhibited acidic composition formulated for efficient removal of rust from steel parts without excessive attack on it. It contains special additives which suppresses fumes for better working environment, prevents itching of surface and thereby metal loss. This results in better rust removal and longer bath life.

Regular additions should be done in the working tank till Fe content reaches maximum limit of 50 gm/lit. Afterwards, the tank solution should be discarded till the solution is effective.

Concentration: 25% - 50% (v/v) v / v = volume by volume

25% RNC 3200 RustoNil v / v = 25 Lit. RNC 3200 RustoNil

+ 75 Lit. water = 100 Lit.

solution

Temperature: Room Temp.

Time: 10 to 30 min @ 30 deg. C

Material of Tank: Plastic or FRP lined MS for dipping application

Shelf life: minimum two years

Packing: 0.5 kg, 1 kg, 5 kg, 20 kg & 50 kg in plastic carboys

Precautions: Nothing in particular, though excessive direct contact with skin should be avoided

## **ASV Multichemie Private Limited**

E 30/3, MIDC Addl. Patalganga, Karade, Tal. Panvel 410 220 INDIA

Tel: +91 93265 01213

Email: info@asvmultichemie.com URL: www.asvmultichemie.com

page 1/1

Date: 23-11-2022