

400°C MoS₂ GREASE



Features:

- The product significantly reduces friction between -25°C and +450°C. In addition to multi-purpose use, it is also used as assembly paste, lubricant and as a release agent at high temperatures. The molybdenum di sulfur content is much higher than similar products.

Operation Range:

- Operating at high temperature up to 600°C; tight and comfortable passes,
- Bushings and gears,
- Automotive industry gear wheel arrangements,
- In sliding and rail bearings and rail joints and shafts that require dry lubrication of the guides and connections of the slide bearings, in rubber plastic parts (o-rings, v-rings, etc., tight fitting parts as mounting paste (bolts, bushings, pins, impellers etc.) (wedge, grooved and notched connections, etc.) conical, wedge sleeve friction lock connections, bolt connections.
- It is used as antisize in high temperature and unfavorable atmosphere, in bearings and similar mechanisms that move at low speed, in staple spindles and swivel parts of card machines in textile industry.

Application:

Apply the product to the surface. Then assemble.

Technical data:

Colour:	black
Odour:	characteristic
Density (at 20 °C):	0,93-0,97 g/cm ³
NLGI Class	2
Corrosion protection	0 - 1 (DIN 51 802)

ART. NR.

W 150 217

W 150 217-16

PACKAGING:

1 KG

16 KG